

TENDER SPECIFICATION

BHEL: PSSR: SCT: 1467

FOR

Civil for Boiler, ESP, Power House, TG, Mill Bay and other Main Plant buildings-Foundation, Super structure including Architectural work & other allied works and Structural steel fabrication & Erection for Power House, Mill Bunker Bay, Pipe & cable rack and allied works for units 1&2 of 2 x 800 MW

at

Yermarus Thermal Power Station, Yermarus,
Raichur Dist, Karnataka

VOLUME-II RATE SCHEDULE (REVISED)



BHARAT HEAVY ELECTRICALS LIMITED

(A Government of India Undertaking)

Power Sector – Southern Region

690, Anna Salai, Nandanam, Chennai – 600 035.

BHARAT HEAVY ELECTRICALS LIMITED
(A Government of India Undertaking)
Power Sector, Southern Region
690, Anna Salai, Nandanam, Chennai – 35

Tender Specification No. BHEL: PSSR: SCT: 1467

for

Civil for Boiler, ESP, Power House, TG, Mill Bay and other Main Plant buildings-Foundation, Super structure including Architectural work & other allied works and Structural steel fabrication & Erection for Power House, Mill Bunker Bay, Pipe & cable rack and allied works for units 1&2 of 2 x 800 MW at Yermarus Thermal Power Station, Yermarus, Raichur Dist, Karnataka

One set of Tender documents consisting of Volume-I and Volume II

BOOK SLNO_____

Issued to

M/s

Refer NIT for Last date of submission

Please note this tender document is not transferable


For and on behalf of
BHARAT HEAVY ELECTRICALS LIMITED

ADDL GENERAL MANAGER / CONTRACTS


Place: Chennai -35

PREAMBLE TO THE SCHEDULE OF QTS. (SOQ)


- 1) Details of the items in this Schedule shall be read in conjunction with the corresponding BHEL's Customer specifications and other documents and shall have precedence over any contrary statement mentioned anywhere in this document.
- 2) The work shall be carried out as per construction drawings (which will be issued progressively during the execution), specifications, the description of the items in this schedule and/or Engineer's instructions. The layout, sizes and details of the building, structures and foundations may vary at a large extent during actual construction.
- 3) Items of work provided in this schedule but not covered in the specifications shall be executed strictly as per instructions of the Engineer.
- 4) Unless specifically mentioned otherwise in the contract, the bidder shall quote his rates for the finished items and shall provide for the complete cost towards fuel, tools, tackle, equipment, constructional plant, temporary works, labour, materials, levies, taxes, transport, layout, repairs, rectification, maintenance till handing over, supervision, shops, establishments, services, temporary roads, revenue expenses, contingencies, overheads, profits and all incidental items not specifically mentioned but reasonably implied and necessary to complete the works according to the contract.
- 5) The rate quoted shall be inclusive of cleaning the site of any vegetations, dressing and leveling etc., required for commencement of site activities. No separate payment will be made towards the same.
- 6) The rate shall also be inclusive of carrying out survey of site to establish levels and coordinates at suitable intervals, from existing grid levels and coordinates furnished by the owner, establish bench marks, setting out the location and levels of the proposed structures, constructions and making references, pillars and other identification marks etc. No separate payment will be made towards the same.
- 7) Engineer's decision shall be final and binding on the contractors regarding clarification of items in this schedule with respect to the other section of the contract.
- 8) Unless otherwise specified in the schedule of items Structural and Reinforcement steel will be issued by BHEL as FREE ISSUE for incorporation in the permanent works as specified elsewhere in this tender document.
- 9) In case of any discrepancy between item description, relevant drawing and/or specification clarification shall be sought at tender stage itself. Otherwise it shall be assumed that the bidder has quoted for the more stringent requirement.
- 10) Refer the relevant clauses in the GCC for payment of additional items and Quantity variation.
- 11) Refer Clause 26.0 in NIT for order of precedence.

|  | TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | |
|--|--|------|-------------------|------------|----------|--------------|----------|
| | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| | | | | in Figures | in words | in Figures | in words |
| 100 EARTH WORK | | | | | | | |
| | Earth work In excavation, backfilling and disposal including necessary men/women, materials, equipment, loading, transportation, unloading, dewatering etc as per specification, drawing and as directed by engineer- in-charge for the following. | | | | | | |
| 101 | Earth work in excavation in all types of soil including ash which can be excavated by any means including setting out, levelling, dewatering (but excluding special type of dewatering viz. well point method), shoring & strutting (wherever required), dressing the sides & bottom, all lifts, ramming/compacting the excavated bottom, stacking, disposal of surplus excavated materials within a lead upto 500 m, spreading/levelling of disposed materials etc all complete for following depths below ground level. | | | | | | |
| a | Depth from ground level but not exceeding 2 m | CUM | 83,365 | | | | |
| b | Depth exceeding 2 m but not exceeding 4 m | CUM | 5,000 | | | | |
| c | Depth exceeding 4 m but not exceeding 6 m | CUM | 2,500 | | | | |
| d | Depth exceeding 6 m but not exceeding 8 m | CUM | 500 | | | | |
| 103 | Earth work in excavation in soft rock (rock without any recovery of excavated materials in the form of hard stone/boulder) including weathered rock which can be excavated by means of crow bar, pick axe, pneumatic rock breaker attachment with excavator machine etc but does not require chiselling or blasting including setting out, levelling, dewatering (wherever required), shoring & strutting (wherever required), dressing the sides & bottom, all lifts, ramming/compacting the excavated bottom, stacking, disposal of surplus excavated materials within a lead upto 500 m, spreading / levelling of disposed materials etc all complete for following depths below ground level. | | | | | | |
| a | Depth from ground level but not exceeding 2 m | CUM | 145,950 | | | | |
| b | Depth exceeding 2 m but not exceeding 4 m | CUM | 60,000 | | | | |
| c | Depth exceeding 4 m but not exceeding 6 m | CUM | 10,000 | | | | |
| d | Depth exceeding 6 m but not exceeding 8 m | CUM | 750 | | | | |
| e | Depth exceeding 8 m but not exceeding 10 m | CUM | 750 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|------|-------------------|------------|--|--------------|--|
| <div>  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant </div> | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 104 | Earth work in excavation in hard rock requiring blasting (but excluding controlled blasting) including wedging, line drilling, pre shearing etc as required, setting out, levelling, dewatering (wherever required), dressing the sides & bottom, all lifts, necessary licenses/statutory clearances for blasting, supply, storage & handling of blasting materials, stacking/disposal of surplus excavated material within a lead upto 500m, spreading / levelling of disposed materials etc all complete for following depths below ground level. | | | | | | |
| a | Depth from ground level but not exceeding 2 m | CUM | 70,000 | | | | |
| b | Depth exceeding 2 m but not exceeding 4 m | CUM | 20,000 | | | | |
| c | Depth exceeding 4 m but not exceeding 6 m | CUM | 25,000 | | | | |
| d | Depth exceeding 6 m but not exceeding 8 m | CUM | 2,500 | | | | |
| e | Depth exceeding 8 m but not exceeding 10 m | CUM | 2,500 | | | | |
| f | Depth exceeding 10 m but not exceeding 15 m | CUM | 1,500 | | | | |
| 105 | Earth work in excavation in hard rock requiring controlled blasting including wedging, line drilling, pre shearing etc as required, setting out, levelling, dewatering (wherever required), shoring & strutting (wherever required), dressing the sides & bottom, all lifts, necessary licenses/statutory clearances for blasting, supply, storage & handling of blasting materials, stacking/disposal of surplus excavated material within a lead upto 500m, spreading / levelling of disposed materials etc all complete for following depths below ground level. | | | | | | |
| a | Depth from ground level but not exceeding 2 m | CUM | 12,150 | | | | |
| b | Depth exceeding 2 m but not exceeding 4 m | CUM | 2,500 | | | | |
| c | Depth exceeding 4 m but not exceeding 6 m | CUM | 1,500 | | | | |
| d | Depth exceeding 6 m but not exceeding 8 m | CUM | 500 | | | | |
| e | Depth exceeding 8 m but not exceeding 10 m | CUM | 250 | | | | |
| 107 | Back filling upto any depth below ground level around foundations, plinths, trenches, drains etc to proper grade and level in layers not exceeding 250 mm thickness using/with selected materials from compulsorily excavated soil available within a lead upto 500m and compacted as specified including re-excavation of stacked earth, watering, ramming/compaction by manual/mechanical means, dressing etc all complete for the following. | | | | | | |
| a | Each layer compacted so as to achieve at least 95% maximum dry density as per IS-2720 (Part-VII) | CUM | 60,000 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|--|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| b | Each layer compacted so as to achieve at least 90% maximum dry density as per IS-2720 (Part-VII) | CUM | 20,000 | | | | |
| c | Each layer compacted so as to achieve at least 85% maximum dry density as per IS-2720 (Part-VII) | CUM | 7,500 | | | | |
| 108 | Back filling upto any depth below ground level around foundations, plinths, trenches, drains etc to proper grade and level in layers not exceeding 250 mm thickness using/with selected materials directly from excavation and compacted as specified including watering, ramming/compaction by manual/mechanical means, dressing etc all complete for the following. | | | | | | |
| a | Each layer compacted so as to achieve at least 95% maximum dry density as per IS-2720 (Part-VII) | CUM | 3,350 | | | | |
| b | Each layer compacted so as to achieve at least 90% maximum dry density as per IS-2720 (Part-VII) | CUM | 6,700 | | | | |
| c | Each layer compacted so as to achieve at least 85% maximum dry density as per IS-2720 (Part-VII) | CUM | 3,350 | | | | |
| d | Each layer compacted so as to achieve at least 75% relative density as per IS-2720 part XIV in case of sandy soils. | CUM | 0 | | | | |
| 109 | Extra over ST No. 101 and 103 to 107 for carriage of excavated earth/selected materials for every 1 km or part thereof beyond an initial lead of 500m. | CUM | 187,500 | | | | |
| 110 | Back filling upto any depth below ground level around foundations, plinths, trenches, drains etc to proper grade and level in layers not exceeding 250 mm thickness using/with approved borrowed soil (borrowed soil to be arranged by the bidder) and compacted as specified including supplying borrowed soil, royalty (if any), watering, ramming/compaction by manual/mechanical means, dressing etc all complete for the following. | | | | | | |
| a | Each layer compacted so as to achieve at least 95% maximum dry density as per IS-2720 (Part-VII) | CUM | 8,650 | | | | |
| b | Each layer compacted so as to achieve at least 90% maximum dry density as per IS-2720 (Part-VII) | CUM | 75,000 | | | | |
| c | Each layer compacted so as to achieve at least 85% maximum dry density as per IS-2720 (Part-VII) | CUM | 1,000 | | | | |
| d | Each layer compacted so as to achieve at least 75% relative density as per IS-2720 part XIV in case of sandy soils. | CUM | 2,500 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| e | Each layer compacted so as to achieve at least 70% relative density as per IS-2720 part XIV in case of sandy soils. | CUM | 1,500 | | | | |
| 111 | Supplying and filling sand upto any depth under floors, around foundations, plinths etc. in layers not exceeding 250 mm thickness and compacted so as to achieve at least 80% relative density as per IS-2720 (Part-XIV) including spreading, watering, ramming/compaction by manual / mechanical means, dressing, royalty (if any) etc. all complete. | CUM | 6,250 | | | | |
| A112 | Providing and laying rubble soling with specified sizes of approved quality hard rock rubble or hand broken hard metal of sizes ranging from 100mm to 230mm, at all position and depths below or above finished ground floor level, below foundations, below flooring, and for providing hard standing etc in one or more layers each of approximately 230mm thickness, hand packing, filling in interstices with quarry spalls, grits and providing a layer of 50mm. thickness (consolidated) of moorum/equivalent locally available approved material over each layer of soling including watering, thoroughly compacting each layer with 10 tonne power roller with minimum 6 passes (or with vibrating plate of approved capacity at places not approachable by power roller) all as per the direction of the Engineer and as per specification. | CUM | 10,000 | | | | |
| A113 | Providing and laying 300 mm thick stone pitching including caulking with 1 cement: 4 sand mortar on the slopes of earth fill/cut with approved quality of rock fragments including materials, testing, necessary excavations if any, compaction etc all complete as per specification, drawing and as directed by the engineer. | CUM | 1,200 | | | | |
| A114 | Earth work in stripping of top soil upto a maximum depth of 0.30m below ground level so as to exclude all debris, grass, vegetation, bushes, trees having girth upto 300mm including roots and organic materials etc for leveling and grading including dressing to specified levels & grades and compacting the graded/stripped surface by manual/mechanical means, disposal of stripped materials within a lead upto 1km etc all complete as per specification, drawing and as directed by the engineer-in-charge. | SQM | 43,365 | | | | |
| 200 CONCRETE WORKS | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| | Providing and placing concrete work including cost of labour, materials and equipment for handling, transportation, batching, mixing, placing, vibrating and curing, (excluding cost of centering, shuttering and reinforcement) with mechanised equipments like batching plant, transit mixer, concrete pump etc. complete as per drawing, specifications and as per direction of engineer in charge for the following. | | | | | | |
| 201 | Concrete of grade M10 (1 part cement, 4 part sand, 8 parts of 40 mm graded aggregate by volume) as filling course at any depth below finished floor level, under and around foundations/floors, mass fill etc. | CUM | 750 | | | | |
| 202 | Concrete of grade M10 (1 part cement, 3 part sand, 6 parts of 40 mm graded aggregate by volume) as lean concrete, levelling course , mud mat under and around foundations/floors at any depth below finished floor level etc. | CUM | 250 | | | | |
| 203 | Concrete of grade M15 (1 part cement, 2 part sand, 4 parts of 40 mm graded aggregate by volume) as lean concrete, levelling course , mud mat under and around foundations/floors at any depth below finished floor level etc. | CUM | 3,750 | | | | |
| 204 | Concrete under floors, paving, plinth protection, pipe encasing, drains etc complete with 20 mm nominal size graded aggregate at any depth below finished floor level of ground floor for the following grades. | | | | | | |
| a | M15 Grade | CUM | 750 | | | | |
| b | M20 Grade | CUM | 4,250 | | | | |
| C | M25 Grade | CUM | 2,750 | | | | |
| 205 | Providing and laying Design Mix cement concrete conforming to IS:456 & IS 10262-2009 for reinforced concrete works with coarse sand and graded hard stone aggregate of 20mm nominal size in foundations/substructure, grade slab, drains, under floors etc at any level below finished floor level of ground floor, any shape, position or thickness etc complete including use of plasticizer/ superplasticizer conforming to IS:9103 (latest) to achieve required slump in concrete all complete as per specification & drawing for the following. | | | | | | |
| a | M25 Grade | CUM | 34,000 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 206 | Providing and laying Design Mix cement concrete conforming to IS:456 & IS 10262-2009 for reinforced concrete works with coarse sand and graded hard stone aggregate of 20mm nominal size in superstructure at any level above finished floor level, any shape, position or thickness etc complete including use of plasticizer/ superplasticizer conforming to IS:9103 (latest) to achieve required slump in concrete all complete as per specification & drawing for the following. | | | | | | |
| a | M25 Grade | CUM | 10,500 | | | | |
| 207 | Providing and laying Design Mix cement concrete conforming to IS:456 & IS 10262-2009 for reinforced concrete works of grade M-30 Grade in machine foundations for TG, ID/FD/PA fans, BFP, Coal mills at all elevations below/above finished floor level except TG deck, TG foundation columns and top decks supported over vibration isolation system including addition of suitable plasticizer conforming to IS 9103(latest) to achieve a slump more than 125mm in concrete as per manufacturer's recommendation with 20 mm nominal size graded aggregate in concrete all complete as per specification & drawing. | CUM | 4,750 | | | | |
| 208 | Providing and laying Design Mix cement concrete as per IS:456 & IS 10262-2009 of grades mentioned below for reinforced concrete works using graded aggregate in top decks of all machine foundations supported on vibration isolation system (excluding supply and installation of vibration system) and top deck of TG foundation at all levels, TG foundation columns including addition of suitable plastisizers conforming to IS9103 to achieve a slump more than 125 mm in concrete as per manufacturers recommendation, preperation of scheme for concreting, getting it approved by engineer, labour, materials, equipment, handling, batching, transporting, mixing, pumping, placing, leveling, vibrating, compacting, curing, testing, cleaning and rendering the exposed surface with cement sand mortar to give a smooth and even surface, maintaining and submitting records of concreting, petrographic examination and potential reactivity of aggregate etc. all complete as per specification, drawing and instructions of engineer, including UPV testing as directed by engineer in charge, rectification of the defects in concreting observed by ultra-sonic pulse velocity (UPV) testing by cement/epoxy grout etc, but excluding formwork, staging, reinforcement, embeddments and temperature control of concrete. Payment terms - a) After casting 75% ; b) After receipt of ultrasonic test report - 25%. | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| b | M35 grade (with 20mm nominal size graded stone aggregate) | CUM | 3,000 | | | | |
| 209 | Extra over St. No. 205 to 208 for controlling of temperature of fresh concrete to less than 23 degree centigrade using ice, including all related arrangements for providing, storing and mixing of ice with water, cooling of aggregates etc. All complete as per specification, drawing and instruction of engineer in charge. | CUM of Concrete | 7,650 | | | | |
| 211 | Providing and encasing of structural steel member with concrete using nominal aggregate size of 12.5mm down. Encased member shall be wrapped with welded wire mesh/chicken wire mesh with proper lap etc. complete as per specification for the following grades. (Payment of welded wire mesh, chicken wire mesh shall be made separately) | | | | | | |
| b | M25 grade | CUM | 150 | | | | |
| 212 | Screed concrete conforming to IS 456 with coarse sand and graded hard stone aggregate 12.5mm/6 mm nominal size on the roof at any level or thickness, drains etc complete as per following. | | | | | | |
| b | 1:1.5:3 (1 part cement, 1.5 part sand, 3 parts of aggregate by volume) | CUM | 375 | | | | |
| 213 | Providing and laying Design Mix cement concrete as per IS:456 & IS 10262-2009 for reinforced concrete works using graded aggregate for Concrete in precast works like roof slabs/trench covers, fins, lintels, chajas, beams, columns, wall panels, facias etc.at all levels in all kinds of work including formwork/moulds, curing, rendering the top exposed surface with cement sand mortar (1:3), handling, storing, transpoting, all leads, erection without damage, setting in position with cement sand mortar (1:3), filling the gaps between adjacent precast units with M30 grade concrete or cement sand mortar (1:3) and including making of holes for bolts for fixing, welding etc.complete with graded aggregate (20/12.5/10 mm) and as per specification and drawing for following grades. | | | | | | |
| a | M 25 grade | CUM | 350 | | | | |
| 214 | Providing and laying Design Mix cement concrete as per IS:456, IS 3370 & IS 10262-2009 for reinforced concrete works using graded aggregate for Concrete in water retaining/conveying structures including addition of suitable plastisizer cum waterproofing cement additives confirming to IS 9103 latest to achieve a slump more than 125 mm in concrete as per manufacturers recommendation and conforming to limits of permeability as per IS 2545 and specification with 20 mm nominal size graded aggregate for following grades. | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| b | M 30 grade | CUM | 12,250 | | | | |
| 215 | Dismantling concrete work for all types of structures at all levels including stacking of servicable material to a lead of 500 m and disposal of unservicable material upto a lead of 2 km, cutting of reinforcement, labour, equipment, safety precautions etc all complete as per drawings, specification and instructions of engineer in charge. | | | | | | |
| a | Plain cement concrete of all grades | CUM | 25 | | | | |
| b | Reinforced cement concrete of all grades | CUM | 55 | | | | |
| 216 | Chipping of concrete in reinforced concrete work, cutting pockets, making openings at all levels and according to shapes, disposal of waste materials upto a lead of 2 km as directed by engineer including equipment, safety precautions, making good the broken surface etc all complete as per specification, drawing, instructions of engineer in charge but excluding cutting of reinforcement . | CUDM | 2,500 | | | | |
| 217 | Extra over and above St No 216 for cutting of reinforcement , all sizes and types including labour, equipment, return of cut reinforcement to store etc all complete as per specification, drawings and instructions of engineer in charge. Measurement shall be on the cross sectional area of reinforcement cut. | SQCM | 100 | | | | |
| 218 | Cutting Reinforced concrete with mechanised tools like Core drilling machine etc. for cutting pockets, holes, cores in slab, beam, column or foundation as per direction of engineer in charge. | CUDM | 500 | | | | |
| 219 | Providing and applying curing compound of approved make where ever required as per manufacturer's specification. | SQM | 10,000 | | | | |
| 300 FORM WORKS | | | | | | | |
| Providing, fixing and removing formwork at any elevations for all structures, as per specifications and including all labour, material, scaffoldings and centering complete including pockets etc. complete as per drawing, specifications and as per direction of engineer in charge for the following. | | | | | | | |
| 301 | Fairface form work with good quality water proof ply wood of required thickness and smooth surface below finished ground floor level for foundations, footings, base of columns, walls, columns, pilasters, beams, mass concrete, trenches etc. | SQM | 124,500 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|---|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 302 | Fairface form work with good quality water proof ply wood of required thickness and smooth surface above finished ground floor level for columns, beams, suspended floors, roofs, lintels, cantilevers, staircases, landings, balconies, domes, arches, circular overhead tanks etc. for all heights. | SQM | 42,500 | | | | |
| 303 | Fairface Formwork with good quality water proof ply wood of required thickness and smooth surface for TG superstructure (above base raft level) including preparation of scheme, designing, submission and approval of staging drawing with sufficient props, braces and ties at every tier of height of approx. 4m for all heights. | SQM | 2,725 | | | | |
| 304 | Providing, fixing and removing formwork in block-outs/pockets and openings (below 0.1 sqm plan area) at all elevations including cutting, formation of all shapes and all other operations required for making the required shape and size all complete as per specification, drawing and instruction of engineer in charge. | | | | | | |
| a | Upto 150 mm depth | Each | 50 | | | | |
| b | Pockets of depths more than 150mm and upto 300 mm depth | Each | 75 | | | | |
| c | Pockets of depths more than 300mm and upto 600 mm depth | Each | 100 | | | | |
| d | Pockets of depths more than 600mm and upto 1000 mm depth | Each | 50 | | | | |
| e | Pockets of depths more than 1000mm and upto 1500 mm depth | Each | 13 | | | | |
| 400 REINFORCEMENT | | | | | | | |
| | BHEL will supply Reinforcement Steel as a free issue. Loading, transporting and unloading from BHEL stores at location described in specification shall be done by bidder. The Steel will be issued to the agency in standard lengths. Reinforcements of 8mm, 10mm & 12mm dia steel may be supplied in coil form and the item below should include cost of decoiling with no extra cost. | | | | | | |
| 401 | Providing, straightening, cutting, bending, placing in position at any level, binding of mild steel reinforcements conforming to grade 1 of IS:432 part 1 in concrete including cost of reinforcement and binding wire, labour, scaffolding, transportation to & from stores etc. all complete as per specifications & drawings. | MT | 150 | | | | |
| 403 | Straightening, cutting, bending, placing in position at any level, binding in position of steel reinforcements of TMT steel of grade Fe-500D or 500EQR confirming to IS:1786 including cost of binding wire, labour, scaffolding, transportation to & from stores etc complete all as per specifications, drawings and as directed by Engineer. | MT | 6,670 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 406 | Providing, straightening cutting, bending, placing in position at any level, binding of mild steel reinforcements in brickwork including cost of reinforcement and binding wire, labour, scaffolding etc. complete all as per specifications & drawings. | MT | 13 | | | | |
| 407 | Straightening, cutting, bending, placing in position at any level, binding in position high yield strength steel reinforcements in brickwork including cost of reinforcement and binding wire, labour, scaffolding etc. complete all as per specifications & drawings. | MT | 25 | | | | |
| 500 WATER PROOFING WORKS | | | | | | | |
| Water proofing works including all labour, material, equipment, transportation, handling, curing, sampling, testing etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 501 | Providing and laying underbed grading plaster with cement mortar 1:4 (1 cement : 4 sand) and average thickness of 25 mm including preparation of surface, batching, mixing, leveling etc. all complete. | SQM | 9,350 | | | | |
| 502 | Providing and laying in-situ light weight foam concrete insulation as per relevant IS Code in suitable panels over roofs followed by a layer of 15 mm thick cement sand plaster 1:5 (1 cement: 5 coarse sand) after the curing period of laid foam concrete and providing of expansion joint at intervals as per the recommendation of manufacturer. The insulating properties shall be such that the thermal conductivity shall not exceed 0.125 Kcal/sqm-hr deg C. Cost shall include making of fillets, cleaning & preparation of surface, expansion joints at suitable intervals etc all complete for following. | | | | | | |
| b | Average 75 mm thickness | SQM | 14,475 | | | | |
| 506 | Providing and applying PU based water proofing treatment with one coat of polyurethane or any other equivalent material based primer with an application rate of minimum 6 sq.m per litre and two successive liquid coatings of high solids content urethane pre-polymers or equivalent material based finish coats as per relevant IS/ASTM standards to form an elastomeric membrane with overall dry film thickness 1.5 mm subject to minimum 500 gm/sqm/coat application rate. Item includes surface preparation, polyscrim cloth /fabric for edges, joints & vulnerable points etc all complete as per specifications and directions of engineer in charge. | SQM | 14,675 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 507 | Providing and laying wearing course consisting of minimum 40mm thick plain cement concrete of grade M15 (1:2:4) with graded aggregate of 12.5mm size cast in panels of maximum size 1.2mx1.2m and reinforced with 0.56 mm dia. galvanised chicken wire mesh and sealing of joints (in grooves of 6mm X 6mm) using silicon /elastomeric compound etc all complete. | SQM | 13,000 | | | | |
| 508 | Providing and laying cement concrete chequered flooring tiles of 22 mm thickness and size 250x250 mm / 300x300 mm conforming to IS 13801 with 8 mm thick 1:4 cement mortar over the top most layer of roofing treatment in pathway and entire equipment area with fine joints including sealing of joints (silicon/elastomeric sealant) etc all complete. (Water proofing paid elsewhere) | SQM | 1,675 | | | | |
| 509 | Providing and applying two coats of bitumen grade 85/25 as per IS 702 (@ 1.7kg/sqm)with 1% antistripping compound conforming to IS 6241 in foundation, wall, column etc on concrete surfaces exposed to soil / ash including surface preparation etc. all complete. | SQM | 100,000 | | | | |
| 511 | Providing and mixing water proofing compound conforming to IS:2645 in concrete or cement mortar all complete. | KG | 693 | | | | |
| 512 | Anti termite chemical treatment of soil with Chloropyrifos emulsifiable concentrates (1%) conforming to IS :8944 all complete. | SQM | 25,000 | | | | |
| 600 JOINTS AND FILLERS | | | | | | | |
| Joins & fillers including all labour, material, equipment, transportation, handling etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 601 | Supplying & installation of bitumen impregnated fibre board confirming to IS 1838 as joint filler at joints in concrete including nailing, coating of both faces with coal tar pitch/bitumin etc. all complete. | | | | | | |
| a | 12 mm wide joints. | SQM | 10 | | | | |
| b | 20 mm wide joints. | SQM | 18 | | | | |
| c | 25 mm wide joints | SQM | 420 | | | | |
| d | 50 mm wide joints | SQM | 1,375 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 602 | Providing and applying polysulphide based sealant conforming to IS:12118 in expansion joints in concrete including cleaning of joints, raking out groove, application of primer, scaffolding etc. all complete for following size grooves: | | | | | | |
| b | 20mmX25mm | RM | 500 | | | | |
| 603 | Supplying and filling in position hot applied bitumin sealing compound (Grade A) confirming to IS 1834 including cleaning, mixing, heating, pouring/injecting sealing compound in gaps in joints including application of primer etc. all complete. | | | | | | |
| c | 20mmX25mm | RM | 1,300 | | | | |
| 605 | Providing and sealing of joints with premium grade silicon sealant (Silpruf of GE silicons or approved equivalent) including cleaning of joints, raking out groove, joint filler tapes, application of primer, curing, scaffolding etc. all complete as per manufacturer's recommendation for following size groove: | | | | | | |
| a | 25mmX25mm | RM | 150 | | | | |
| 606 | Providing and fixing PVC water stops in joints conforming to IS 12200 & IS 15058 all complete for the following: | | | | | | |
| d | 230 mm wide and 6 mm thick | RM | 713 | | | | |
| 607 | Providing and fixing copper water stops in joints of deep underground structure all complete for the following: | | | | | | |
| b | 230 mm wide and 8 mm thick | RM | 150 | | | | |
| 700 MS EMBEDMENTS | | | | | | | |
| Embedments including all labour, material, equipment, transportation, handling etc. at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 701 | Supply, fabricating and fixing of mild steel embedments, inserts, pipe sleeves, angle pieces, rungs of various diameters, plates of dimensions as required etc. including welding, bolting, cutting, drilling, scaffolding, setting etc. all complete. | MT | 150 | | | | |
| 702 | Same as above with BHEL supplied raw material free of cost including loading, transportation, unloading etc. all complete from BHEL store to plant site. | MT | 25 | | | | |
| 703 | Supply and fixing of embedments, inserts, pipe sleeves, angle pieces, anchor bolts of various diameters, plates of dimensions as required etc. including scaffolding, setting in position, transportation from BHEL site stores to work spot etc. all complete. | MT | 25 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 704 | Supply, Fabrication, transportation, delivery at site and erection, installation and alignment of mild steel foundation bolt assembly conforming to IS:2062 and grade 1 of IS:432 in concrete along with nuts, lock nuts (as per IS:1363, 1364 and IS:3138), washers, anchor plates, stiffner plates, protective tape, pipe sleeves, templates etc. including welding, cutting, grinding, threading, drilling etc. all complete. | MT | 120 | | | | |
| 705 | Supplying, fabricating, erecting and installing following items in concrete/brickwall for all kind of works, including setting material in concrete, layout, scaffolding, cutting, forming, grinding, drilling, bolting, welding, jointing, testing etc. all complete. | | | | | | |
| a | MS pipes of all diameters | Quintal | 77 | | | | |
| b | PVC pipes / conduits of all diameters | Quintal | 25 | | | | |
| d | Expansion fasteners (mechanical & galvanised) of HILTI make or equivalent of safe tensile capacity as specified below for brick work/M25 grade of concrete with expansion sleeve | | | | | | |
| i | Upto 250 kg | Each | 100 | | | | |
| ii | Beyond 250 Kg and upto 500 kg | Each | 100 | | | | |
| iii | Beyond 500 Kg and upto 750 kg | Each | 100 | | | | |
| e | Chemically fixed anchor fasteners (galvanised) of HILTI make or equivalent of safe tensile capacity as specified below for concrete work of grade M25 or above. | | | | | | |
| i | Upto 250 kg | Each | 150 | | | | |
| ii | Beyond 250 Kg and upto 500 kg | Each | 150 | | | | |
| iii | Beyond 500 Kg and upto 750 kg | Each | 100 | | | | |
| A705 | Providing and fixing Rebar (reinforcement bar) with Hilti or equivalent Resin bonded epoxy fixing method including anchor fastener, materials, equipment, labour, scaffolding complete as per direction of Engineer. Cost of reinforcement bar is not to be included in this item. Rebar has to be designed for full strength in M30 grade of concrete and the depth of embedment is to be provided accordingly. | | | | | | |
| i | 12mm Diameter bar | Each | 150 | | | | |
| ii | 16mm Diameter bar | Each | 200 | | | | |
| iii | 20mm Diameter bar | Each | 100 | | | | |
| 800 GROUTING | | | | | | | |
| Grouting including all labour, material, equipment, roughening surface, cleaning, ramming, curing etc. at any level unless otherwise specified as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 801 | Providing & grouting with cement slurry mix of approved ratio using pressure pump for water retaining concrete structures as per approved procedure including cost of nipples/ nozzles, cement, admixture, curing, pressure pumps, slurry agitator etc. all complete. Cost shall include fixing of nipples at minimum 500 mm centre to centre spacing, cutting of nipples after completing of grouting, making good of the nipple hole with appropriate non-shrink cement paste, water tightness test etc. all complete wherever specified in the drawing. | SQM | 805 | | | | |
| 803 | Providing & grouting of pocket holes, pipe sleeves and under base plate of structural steel work/ machinery/ pipe supporting structures including roughening of surface, cleaning, ramming, curing etc. all complete with mix 1:1:2 (1 cement : 1 coarse sand : 2 aggregate of 6 mm down graded stonechips) using non shrink admixture. (Cost of all material and cleaning the pocket by compressed air shall be in the scope of the contractor). | CUM | 28 | | | | |
| 804 | Providing & grouting of pocket holes, pipe sleeves and under base plates of structural steel work/ machinery/ pipe supporting structures including roughening of surface, cleaning, ramming, curing etc. all complete with ConbextraGP-1 or equivalent . (Cost of all material and cleaning of the pockets by compressed air shall be in the scope of the contractor). | CUM | 75 | | | | |
| 805 | Providing & grouting of pocket holes, pipe sleeves and under base plates of structural steel work/ machinery/ pipe supporting structures including roughening of surface, cleaning, ramming, curing, etc. all complete with Conbextra GP-2 or equivalent . (Cost of all material and cleaning of the pockets by compressed air shall be in the scope of the contractor). | CUM | 30 | | | | |
| 900 DOORS, WINDOWS, VENTILATORS, LOUVERS | | | | | | | |
| Doors, windows, ventilators, louvers, roof ventilators, rolling shutters, partitions including all labour, material, equipments, transportation, handling, preparation of working drawings etc. at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 901 | Providing and fixing wooden frame conforming to IS 4021 made of best quality seasoned CP teakwood free from large or loose knots, cracks or other defects including sand paper smoothening, hold fasts, beading, primer and finish painting / polishing etc. all complete with proper wood joinery, accurately set to required lines or levels and rigidly secured in place. (Finish painting / polishing paid separately) | CUM | 5 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 902 | Providing and fixing teakwood frame panel door shutter as per IS 1003 with 35 mm x 150 mm vertical rail & 35mm x 125 mm horizontal rail and 12 mm thick interlocked panels of teakwood with proper wood joinery including beading, preperation of working drawings,godrej or equivalent make mortice lock with handels on both sides,approved ISI mark anodised fittings like door stopper,300mm long tower bolts,16x300mm long aldrops ,125mm long handles on both sides etc. butt hinges, sliding bolt ,knobs, (all fitting shall be anodised aluminium color dyed), screws, primer and finish painting / polishing etc. all complete. (Finish painting / polishing paid separately) | SQM | 25 | | | | |
| 904 | Providing and fixing single or double steel door shutters with 45mm thk flush design shutter comprising of two outer sheets of 18 gauge steel sheets rigidly connected and reinforced inside with continuous vertical 20 gauge stiffeners, spot welded in position at not more than 150mm on centres including void filled with mineral wool (density as per specification), all fittings, Godrej or equivalent make mortice lock with handle on both sides, tower bolt, stopper, aldrops, shop and final painting etc all complete. | SQM | 270 | | | | |
| 906 | Providing and fixing anodized extruded aluminium doors (single or double shutter) conforming to IS:1948, IS:1949 fabricated from extruded sections of INDAL or equivalent make having minimum 3mm wall thickness as per IS:1285, IS:733 and anodized and electro color coating of required shade as per IS 1868 (minimum anodized coating of grade AC15). fixed with rawl plugs, expansion fasteners,SS screws / fixing clips necessary filling of gaps at Junctions, at top, bottom & sides with required PVC / neoprene felt for bi-metallic protection etc. Glazing shall be fixed with snap fit type beading, concealed screws, fixtures, Godrej or equivalent make Mortice lock with handle on both sides, etc all complete. Aluminium section shall be smooth, free of stains, straight, mitred & jointed mechanically wherever required. (Glazing shall be paid separately). | SQM | 100 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|------|-------------------|------------|--|--------------|--|
| <div>  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant </div> | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 907 | Providing and fixing fire proof steel doors (single or double shutter) with panic devices shall be 45mm thk flush design comprising of two outer sheets of 18 gauge steel sheets rigidly connected and reinforced inside with continuous vertical 20 gauge stiffeners, spot welded in position at not more than 150mm on centers including all fittings, shop painting with approved post office/signal red color fire resistant paint and mineral wool insulation (64 kg/cum density) complete and shall be fire proof as per IS:3614, TAC requirements and as per specification. Minimum ratings shall be 2 Hrs. | SQM | 200 | | | | |
| 908 | Providing and fixing steel windows/ventilator with steel sections as per IS:1038, IS:1361 & IS:7452 latest revision.including all fittings, metal beadings, hold fasts, shop and final painting ,glazing etc. all complete. (Glazing shall be paid separately) | | | | | | |
| a | openable type | SQM | 125 | | | | |
| b | fixed type | SQM | 100 | | | | |
| 909 | Providing and fixing anodised aluminium work of INDAL or other equivalent approved make for door frames, windows, ventilators, partitions, railing etc with extruded standard tubular and other sections including all fittings & fixtures and accessories of approved make conforming to IS733 and IS1285, anodised and electro color dyed to required shade according to IS 1868 (minimum anodic coating of grade AC15), fixed with rawl plugs, expansion fasteners, SS screws or with fixing clips, including necessary filling of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt for bi-mettalic protection etc.including preperation of working drawings, aluminium cleat angle, aluminium snap-on-beading for glazing/panelling, stair case tread nosing, with all fittings and fixtures (like tower bolts, handles, door stopper with rubber shoes, 'L' drops, stays, floor springs, hydraulic door closures etc.), CP brass/stainless steel screws, providing and fixing hinges/pivots, and making provision for fixing of fitting wherever required including cost of PVC/neoprene gasket, all complete as per drawing, specification and instructions of engineer in charge (Glazing and panelling shall be paid seperately).Weight of finished aluminium section only shall be measured. | Kg | 2,000 | | | | |
| 911 | Providing and fixing of door closers as per IS 3564 ,of approved make & quality all complete of following type : | | | | | | |
| a | Over head hydraulic door closures | Each | 85 | | | | |
| b | Floor mounted Hydraulic door closers | Each | 33 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 912 | Providing and fixing pressed steel frames fabricated from 16 gauge M.S sheet mortised, reinforced drilled and tapped for hinges and locks bolts strikes, hold fasts adjustable floor anchors, floor tiles/weather bars ,paintings etc all complete as per specifications. | Kg | 2,800 | | | | |
| A912 | Providing, fitting and fixing heavy duty minimum six lever mortised lock of godrej or equivalent make with handles or knobs to single and double leaf door (wooden/steel/aluminium) with duplicate set of keys and masterkeyed locks, openable from one side by the key and from the other side by the handle, etc. all complete as per drawing, specification and instruction of engineer in charge | Each | 93 | | | | |
| 913 | Providing and fixing in position rolling shutter of hot rolled double dipped galvanised steel lath section of 18 SWG tested mild steel strips at 75mm rolling centres interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation including wire springs, top cover, primer & shop coats of approved enamel paint etc, all complete as per IS 6248 and specification of approved make of following types: The bottom lath shall be coupled to a lock plate fabricated from 3mm thick galvanised steel plate and securely rivetted with stiffening angles.(partly coiled and lath/full lath). | | | | | | |
| a | Hand operated | SQM | 50 | | | | |
| b | Mechanically Operated | SQM | 150 | | | | |
| c | Electrically operated | SQM | 200 | | | | |
| 914 | Providing and fixing PVC doors(25 thk double skin) of sintex or equivalent make including all fitting & fixtures, door frame as per specification, drawing and instructions of engineer in charge. | SQM | 50 | | | | |
| 915 | Providing, fixing and fitting of glazing of first grade class in steel/aluminium/wooden frames, where ever required, cleaning after fixing including hardware, gaskets, clips, beadings etc. all complete. | | | | | | |
| b | 4 mm thick clear float glass | SQM | 470 | | | | |
| c | 5.5 mm thick clear float glass | SQM | 675 | | | | |
| d | 6 mm thick wired glass | SQM | 1,008 | | | | |
| e | 6mm thick Polycarbonate sheet multi (twin) wall fire retardant and ultra violet resistant with sealed open edges. | SQM | 118 | | | | |
| f | 4 mm thick ground glass | SQM | 125 | | | | |
| g | 6 mm thick heat reflecting type float glass | Each | 10 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| h | 6 mm thick clear toughened safety glass | SQM | 275 | | | | |
| i | Two nos. 6 mm thick clear toughened float glass hermetically sealed and separated by 12 mm thick air gap for thermal insulation (only single elevation area to be measured) | SQM | 165 | | | | |
| j | Two nos. 6 mm thick tinted toughened float glass hermetically sealed and separated by 12 mm thick air gap for thermal insulation (only single elevation area to be measured) | SQM | 88 | | | | |
| k | One outer 6mm thick tinted heat-reflecting type float glass and one inner 6mm thick plain float glass hermetically sealed and seperated by 12 mm thick gap for thermal insulation (only single elevation area to be measured). | SQM | 800 | | | | |
| l | 6 mm thick laminated glass | SQM | 590 | | | | |
| A915 | Providing and fixing base Glass panel door (double leaf) for entrance of approximate size (3mX3m) manufactured with minimum 15mm thick plain toughened glass. This includes stainless steel heavy duty handle fitted in glass, top & bottom hinged, heavy duty floor spring of approved make for both panel of doors. All the fittings, fixtures & installation shall be of high quality to ensure smooth & stable operation of glass door on long term basis. | SQM | 5 | | | | |
| 916 | Supplying and fixing weather stripping of approved make and quality to doors as per instructions of engineer in charge and specification complete. | RM | 100 | | | | |
| 917 | Providing and fixing factory made pre-laminated particle board (MDF exterior grade) fixed with necessary fittings etc. all complete with 35x12 mm thick teakwood beading all around including godrej or equivalent make mortice lock with handels on both sides,approved ISI mark anodised fittings like door stopper,300mm long tower bolts,16x300mm long aldrops ,125mm long handles on both sides etc. butt hinges, sliding bolt, knobs, (all fittings shall be anodised aluminium color dyed), finish synthetic paint over primer, screws etc. all complete as per drawing, specification and instruction of engineer in charge. with commercial faces and teak wood edges. (Finish painting paid separately) | SQM | 100 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|---|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 920 | Roof skylight structure for atrium with 6mm thick Polycarbonate sheet multi (twin) wall fire retardant and ultra violet resistant with sealed open edges for sky light for approved shape like dome, pyramidal etc. Joints are properly sealed with sealant, screws with pvc cap, self tapping screws, epdm rubber gasket.etc all complete as per detailed drawing and specification. | SQM | 300 | | | | |
| 1000 BRICKWORK | | | | | | | |
| Brickwork masonry including all labour, material, equipment, transportation, handling, scaffolding etc. at all levels as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 1001 | Providing brick work in cement mortar 1:6 (1 part cement 6 parts coarse sand) in walls, chambers etc. in thickness varying from 230mm to 460mm at all depths, places and positions below plinth including raking out joints, curing, scaffolding etc. complete excluding plastering and painting. | | | | | | |
| a | Using fly ash lime bricks confirming to IS 12894 with crushing strength of 75 kg/cm ² | CUM | 750 | | | | |
| d | Using burnt clay bricks of class designation 5.0 of nominal dimension | CUM | 350 | | | | |
| 1002 | Providing brick work in cement mortar 1:6 (1 cement 6 coarse sand) in walls, chambers etc. in thickness 230mm at all heights, places and position above plinth including raking out joints, curing, scaffolding etc complete excluding plastering and painting. | | | | | | |
| a | Using fly ash lime bricks confirming to IS 12894 with crushing strength of 75 kg/cm ² | CUM | 3,000 | | | | |
| d | Using burnt clay bricks of class designation 5.0 of nominal dimension | CUM | 1,300 | | | | |
| 1003 | Providing brick work in cement mortar 1:4 (1 cement 4 coarse sand) in partition walls , chambers etc. in thickness 115mm for clay brick and 100mm for flyash brick at all heights, places and position above or below plinth/graded level including providing two nos. 6 mm diameter MS bars at every third layer, raking out joints, curing, scaffolding etc complete excluding plastering and painting as per specification. | | | | | | |
| a | Using fly ash lime bricks confirming to IS 12894 with crushing strength of 75 kg/cm ² | SQM | 1,000 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|---|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| d | Using burnt clay bricks of class designation 5.0 of nominal dimension | SQM | 350 | | | | |
| 1005 | Providing brick soling including spreading of earth, ramming, watering including 25mm thick cushion of sand complete but excluding excavation and disposal of surplus earth (excavation and disposal of surplus earth shall be measured under applicable item.).- Using flat bricks. | | | | | | |
| a | Using fly ash lime bricks confirming to IS 12894 with crushing strength of 75 kg/cm ² | SQM | 250 | | | | |
| d | Using burnt clay bricks of class designation 5.0 of nominal dimension | SQM | 250 | | | | |
| 1006 | Breaking of existing brick work at all levels including plastering, removing the rubbish up to a distance of 500 m including transportation, loading, unloading etc. all complete as directed by the engineer. | CUM | 25 | | | | |
| 1007 | Providing and encasing of structural steel member with masonry work around flanges, webs etc. and filling the gap between steel and masonry by minimum 12mm thick mortar. Encased member shall be wrapped with chicken wire mesh with 50mm lap etc. complete as per specification. (Chicken wire mesh to paid separately) | CUM | 115 | | | | |
| 1009 | Making openings in existing brick wall or partition wall including making good the broken edges/surface with cement mortar etc. complete. | CUM | 75 | | | | |
| 1010 | Supply and placing in position mild steel wire fabric of square mesh 25 mm size and wire diameter of 2 mm for encasing of steel sections in concrete including cutting, bending, fixing etc. complete. | SQM | 1,250 | | | | |
| 1011 | Filling existing brick wall/ partition wall opening at all level including making good the broken edges/surface with cement mortar, painting, finishing to match with existing finishing, scaffolding/supporting at any level, removal of debris upto a lead of 1 km including loading, unloading, transportation etc. all complete. | SQM | 25 | | | | |
| 1012 | Providing and filling brick bats in soak pits all complete. | CUM | 38 | | | | |
| A1013 | Providing 115mm thick brick work in cement mortar 1:4 (1 part cement 4 parts coarse sand) in lining for surface drain over ground at slope as per drawing with flush pointing in cement mortart 1:2. complete excluding plastering and painting. | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|--|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| a | Using fly ash lime bricks confirming to IS 12894 with crushing strength of 75 kg/cm ² | SQM | 375 | | | | |
| b | Using burnt clay bricks of class designation 5.0 of nominal dimension | SQM | 375 | | | | |
| 1100 DAMP PROOF COURSE | | | | | | | |
| Damp proof course including all labour, material, equipment, transportation, handling, shuttering, centering, curing etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 1101 | Providing Damp Proof Course 50mm thick 1:1.5:3 concrete (10mm and down graded aggregate) with 2% of approved admixture of water proofing compound all complete. Two layers of hot bitumen coating 85/25 grade as per IS:702 @ 1.7Kg./sqm shall be applied one before & one after the DPC. | SQM | 210 | | | | |
| 1200 CEMENT MORTAR PLASTER | | | | | | | |
| Cement mortar plaster including making grooves wherever required including all labour, material, scaffolding, curing etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 1201 | Providing 20mm thick plaster in two layers (14mm of 1:6 cement mortar + 6mm of 1:4 cement mortar) outside the building/boundary wall on walls, finished to a smooth finish including providing 3mmx3mm size grooves at junctions of two dissimilar materials all complete including use of approved water proofing compound. | SQM | 25,100 | | | | |
| 1202 | Providing 13mm thick plaster inside the building/boundary wall in cement mortar 1:6 on even side of walls finished to a smooth finish as per specification all complete. | SQM | 12,650 | | | | |
| A1202 | Providing 18mm thick plaster inside the building/boundary wall in cement mortar 1:6 on uneven side of walls finished to a smooth finish as per specification all complete. | SQM | 12,650 | | | | |
| 1203 | Providing 12mm thick plaster in cement mortar 1:6 on walls with rough finish all complete. | SQM | 7,700 | | | | |
| 1204 | Providing 6mm thick plaster on ceiling in cement mortar 1:4 finished to a smooth all complete. | SQM | 21,000 | | | | |
| 1205 | Providing 12mm thick plaster in walls, drains/culverts with a paste of neat cement @ 1kg/sqm and rubbed smooth with trowel etc. all complete. | SQM | 1,950 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|---|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1206 | Providing and making decorative plaster of all types and design on walls, ceilings, arcs, columns with various thickness upto 18 mm including finishing all complete. | SQM | 3,250 | | | | |
| 1207 | Forming groove of uniform size from 12X12 mm upto 20X15 mm in plastered surface as per approved pattern, using wooden battens nailed to the under layer, including removal of wooden battons, repair of the edges of plaster panel and finishing the groove etc. complete as per specification, drawing and the instructions of engineer in charge. | RM | 175 | | | | |
| 1208 | Providing drip coarse on plastered surface at all elevations for all type of work such as chajjas, parapet, projections etc. including scaffolding, finishing etc. complete with all labour, tools and plants as per specification, drawing and instructions of engineer in charge. | RM | 125 | | | | |
| 1209 | Providing and laying encasement to box type steel beams at all levels with lath plaster 50 mm nominal thickness with cement plaster (1:4) over chicken wire mesh including all labour, materials, equipment, handling, transporting, mixing, placing, leveling, curing and cleaning, finishing the exposed surfaces etc including centering and shuttering all complete as per specification, drawing and instructions of enginner in charge (chicken wire mesh to be paid separately) | SQM | 2,600 | | | | |
| 1210 | Ruled pointing in masonry in CM 1:3 (1 cement and 3 fine sand) including raking out joints, curing etc. complete. | SQM | 250 | | | | |
| 1300 FINISHES TO CONCRETE / PLASTERED SURFACES | | | | | | | |
| Finishes, painting to concrete, plastered surfaces including all labour, material, equipment, surface preparation, scaffolding etc. at any level as per specification, drawings and as directed by engineer - in - charge. For painting on concrete, masonry and plastered surfaces, IS:2395 parts I and II shall be followed. For painting on wood work IS:2338 part I & II shall be followed. All paints shall be of brand and make to the approval of OWNER. A minimum of two finishing coats of paint over a coat of primer shall be provided to give a smooth uniform finish for the painted surface. All painting on masonry or concrete surfaces shall preferably be applied by rollers. Thinner shall not be used with textured paint finish. | | | | | | | |
| 1301 | Two or more coats of white wash/ colour wash as per IS 627 of approved brand and manufacture to give an even shade including a priming coat as per specifications. | SQM | 2,500 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|------|-------------------|------------|--|--------------|--|
| <div>  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant </div> | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1303 | Providing and applying two or more coats of oil bound destemper as per IS 428 of approved brand, shade and manufacture to give smooth, hard, durable & glossy finish over a coat of primer over prepared plaster surface as per manufacturers guideline. | SQM | 3,375 | | | | |
| 1306 | Providing and applying 2 or more coats of acid/alkali resistant paint of approved brand and colour to floors, walls and ceiling including preparation of surface to receive paint, providing and applying bitumen primer confirming to IS 158 complete all as per manufacturer's recommendations and as approved by engineer, at all heights above or below grade level, complete as per specifications. | SQM | 3,875 | | | | |
| 1307 | Two or more coats of fire resistant transparent paint as per IS 162 on all woodwork over french polish as per IS 348 or flat oil paint as per IS 137 of approved grade and manufacture to give an even shade as per specifications. | SQM | 250 | | | | |
| 1308 | Two or more coats of black anti-corrosive bitumastic painting of approved brand and manufacture to give an even shade complete. | SQM | 100 | | | | |
| 1309 | Two or more coats of synthetic enamel paint of approved make made from synthetic resins and drying oil with rutile titanium dioxide and other selected pigments to give smooth, hard, durable & glossy finish to all interior and exterior wooden surfaces complete. | SQM | 250 | | | | |
| 1310 | Providing and applying 3 coats of water proof cement paint of approved make and color on exterior surface at all heights including material, labour, scaffolding, curing etc including primer coat complete as per specification. | SQM | 6,000 | | | | |
| 1311 | Providing and applying resin bonded granular textured finish of Sandtex matt or equivalent, for external applications shall consist of crushed stone/quartz chips of .5 mm to 2.5 mm size and of approved natural color/shade and bonded with synthetic resins, adhesives and additives altogether in a single pack mix, applied on cured and dried plaster surface with a dry film thickness of minimum 2 mm. The final finish shall have UV resistance, fungus, bacterial resistance properties all complete with grooves filled with poly sulfide sealant of matching color and shade as per specification/drawing/approval of engineer in charge. | SQM | 1,050 | | | | |
| 1312 | Providing and applying 2 mm thick plaster of paris punning on walls including preparation of surface, staging, etc. to achieve a smooth even surface all complete as per specification and as directed by Engineer. | SQM | 18,400 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|------|-------------------|------------|--|--------------|--|
| <div>  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant </div> | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1313 | Providing and applying ready made Epoxy Paint over areas other than steel structure with suitable pigments of approved shade as per specification and direction of Engineer. The epoxy paint shall be a two pack material and shall be resistant to water, splash, spillage & acidic environment. The epoxy paint coating shall be of 150micron thickness over epoxy primer. | SQM | 675 | | | | |
| 1315 | Providing and applying two or more coats of Acrylic emulsion paint of approved brand and manufacture and required shade over one coat of primer after necessary cleaning/ washing, preparing the surface using coir brush/ wire brush, sand paper, including filling of cracks with putty wherever required etc. all complete to give smooth, hard, durable & glossy finish over a coat of primer over prepared plaster surface as per manufacturers guidelines. The final finished coating shall be fungus resistant, UV resistant, water repellent and extremely durable with color fastness as per specification. | SQM | 25,000 | | | | |
| 1400 FLOORING AND SKIRTING | | | | | | | |
| Flooring and skirting at any level including base layer, labour, material, equipments, transportation, handling, curing, polishing etc. at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 1401 | Providing and laying 50 mm thick heavy duty cement concrete in flooring with metallic hardener pigmented topping 12mm thick uniform graded treated iron particles in flooring. Under layer of 38mm thick cement concrete mix 1:2:4 (1 cement: 2 sand : 4 stone aggregates 12.5mm well graded) and top layer of 12mm thick metallic concrete of mix 1:2 (1 cement hardner mix with approved quality metallic hardening compound :2 stone aggregate 6mm nominal size) by volume including cement slurry, rounding off edges, aluminium strips etc. all complete for following (Quoted item rate shall be inclusive of providing glass joint strips): | SQM | 24,725 | | | | |
| 1402 | Providing and laying 25 mm thick heavy duty cement concrete mix 1:2:4 (1 cement: 2 sand : 4 stone aggregates) flooring with metallic hardener pigmented topping of 10 mm thick uniform graded treated iron particles in skirting and dado complete as per specification. | SQM | 1,000 | | | | |
| 1405 | Providing and laying 50 mm thick floor finish with 25mm thk Terrazo Tiles of size 250mm x250mm including cement mortar bedding of 1:3 (1 cement : 3 sand) with neat cement slurry etc. all complete. | SQM | 175 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1406 | Providing and laying polished Kota stone 18mm to 20mm thk in flooring . Under bed shall average 30mm thk of 1 cement : 2 sand : 4 stone aggregates by volume and brought to proper level. The kota stone slabs/tiles laid over under bed, pressed and tapped down with wooden mallet to the proper level, lifted and pressed again with thick cement slurry spread over the surface with fine joint finished including pigments, curing, grinding, granite polishing etc. all complete. | SQM | 190 | | | | |
| 1412 | Providing and laying 18-20mm thick polished Granite stone of approved color and texture in flooring with brass/ stainless steel strips. Under bed shall average 30mm thk of 1 cement : 2 sand : 4 stone aggregate by volume and brought to proper level. The granite stone slabs/tiles laid over under bed, pressed and tapped down with wooden mallet to the proper level, lifted and pressed again with thick cement slurry spread over the surface with fine joint finished including pigments, curing, grinding, granite polishing etc. all complete. | SQM | 3,000 | | | | |
| 1415 | Providing and laying polished Granite stone 14-16mm thk in skirting and dado with 6mm thick projection from adjacent plaster including mortar ,cement slurry ,pigments, curing, grinding,moulding, granite polishing etc. all complete. | SQM | 125 | | | | |
| 1416 | Providing and laying vitrified ceramic tiles of polished variety of size 600x600 from reputed / approved manufacturer, complete including underbed of cement mortar 1:3 with neat cement slurry etc. all complete for following | | | | | | |
| b | 10mm thick tiles In flooring & skirting | SQM | 1,500 | | | | |
| 1417 | Providing and laying vitrified ceramic tiles of matt finish of size 600x600mm from reputed / approved manufacturer including underbed of cement mortar 1:3 with neat cement slurry etc. all complete for following. | | | | | | |
| a | 7mm thick tiles In flooring | SQM | 400 | | | | |
| c | 7mm thick tiles In skirting and dado upto specific height | SQM | 390 | | | | |
| 1419 | Providing and laying granite stone slab of 20mm thickness single piece for wash basin / sink slab /facia of black or approved colour with cutting,making corners,moulding and opening etc. all complete. | SQM | 50 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1421 | Providing and laying Heavy Duty dust pressed (grade-5) Ceramic Tiles (Matt Finish) of size 600x600mm(approved size) and 7mm thick of reputed / approved manufacturer (Kajaria,jhonson,Spartek or equivalent) of approved finish, shade and colour. The tiles shall be scratch resistance of minimum 5 on Mohr's scale and shall have a bending strength of 350 Kg./sqm,with Under bed shall average 43mm thk of 1 cement : 2 sand : 4 stone aggregates by volume and brought to proper level including cement mortar all complete. | SQM | 400 | | | | |
| 1422 | Providing & fixing Acid / Alkali resistant (Chemical resistant) tiles confirming to IS:4457 in flooring/Dado and shall be laid over bitumastic lining of min 12mm thick (to be laid in layers of 6mm each). The tiles shall be applied with 6mm thick Potassium Silicate bedding mortar as per IS:4441, 4443 & 4832 and including preparation of surface, application of bitumen primer, curing etc. all complete for following thicknesses. The tiles should be abrasion resistant & durable. | | | | | | |
| a | 25mm thick tiles and 50mm total floor thickness | SQM | 600 | | | | |
| 1424 | Providing & fixing chemical resistant (AR)(Acid / Alkali) bricks (75mm thick) conforming to IS:4860 in the floor of neutralization pit. Surface on which lining to be applied shall be prepared in accordance with IS:2395. Bitumen primer as per IS:158 followed by 18mm thick bituminastic followed by 6mm thick potassium silicate mortar bedding shall be provided before laying AR bricks. The joints between AR bricks shall be filled with resin type of mortar conforming to IS:4832, part II, seal coat of readymade epoxy paint shall be provided on joints to cover up any porosity that may be left in mortar. End sealing shall be done with bituminastic AR bricks shall be laid with 6mm wide & 50mm deep pointing (epoxy / furnace / CNSL) & acid curing shall be done all complete as per specification. | SQM | 100 | | | | |
| 1426 | Providing and laying marble skirting /dado (Aranga white or approved shade/color /design) equivalent of minimum 20mm thickness projecting 6mm from adjacent plaster all complete including underbed cement mortar 1:3, scaffolding etc. all complete. | SQM | 35 | | | | |
| 1427 | Providing and fixing glazed ceramic tiles of approved color and design of size 200x300mm / 300x300mm in dado of approved size, projecting 6mm uniformly from adjacent plaster or wall finish. The mix for underbed plaster shall consist of 1part cement and 3 parts sand by weight. fairly moist but firm, tiles shall be pressed over under bed by applying cement slurry including pigments, curing etc all complete for following thicknesses: | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| b | 7mm thick | SQM | 125 | | | | |
| 1428 | Providing and laying 3mm thick antistatic PVC flooring / skirting of approved shade,as per IS:3462 and laying as per IS:5318 all complete. | SQM | 175 | | | | |
| 1429 | Providing and fixing removable type flooring system consisting of fire resistant particle board of size 600X600X35 mm with 0.05 mm thick aluminium foil lining at bottom and with 2 mm thick anti static PVC topping including proprietary floor supporting system complete as per specification. | SQM | 2,900 | | | | |
| 1430 | Providing and fixing dividing strips in joints of cast in situ floorings at various elevations, finishing, all labour, material etc. complete as per drawing, specification and instructions of engineer in charge. | | | | | | |
| a | Glass strips 40 mm wide and minimum 6 mm thick. | RM | 5,100 | | | | |
| b | Aluminium strips 40 mm wide and minimum 3 mm thick | RM | 5,100 | | | | |
| A1431 | Providing and applying ready made Epoxy floor coating of approved make over concrete surface of floor with suitable pigments of approved shade as per specification of manufacturer and direction of Engineer. The epoxy paint shall have primer coat as well numbers of finish coat to give an even surface as per Engineers direction and shall be resistant to water, splash, spillage. | SQM | 50 | | | | |
| 1500 ROOFING / SIDE CLADDING | | | | | | | |
| Roofing / side cladding work including all labour, material, equipment, transportation, handling, scaffolding, laps, hooks, washers, corner pieces etc. at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|---------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1501 | Designing, providing and fixing permanently color coated galvanised MS troughed metal sheet decking plate of approved colour and conforming to class3 of IS 14246 over roof purlins for cast-in-situ roof slab as per relevant IS code and specification. Bare metal thickness of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm having minimum yield strength of 250 MPa and shall serve as permanent shuttering to the roof slab 100mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 150 kg/sqm during construction between purlins as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to purlins, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyester paint of minimum 20 micron DFT on exposed surface (facing operating floor) and minimum 7 micron on other face over epoxy primer applied over hot dipped galvanising @ 275 gm/sqm including fixing of sheet to purlin with self drilling white zinc plated heat treated carbon steel screws of minimum 5.6 mm dia @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. Measurement of profile sheeting shall be of the plan area of roof covered by MS trough metal decking. | | | | | | |
| a | Span Upto 1800mm | SQM | 9,000 | | | | |
| 1502 | Providing and fixing shear connectors of mild steel studs having 16mm dia and minimum 75 mm projected length above purlin passing through metal decking as per relevant IS codes and specification. | QUINTAL | 20 | | | | |
| 1503 | Designing, providing and fixing External sheet of Permanent colour coated metal cladding with troughed M.S. sheets of 0.6mm bare metal thickness having minimum yield strength 250 MPa and zinc-aluminium alloy coating not less than 275 gm/sqm total on both sides including fixing to supports / rails by concealed fixing system, corrosion resistant self tapping / self drilling type fasteners with suitable cap, flashing etc. all complete. The exposed face of the sheet shall be permanently colour coated with Polyfluro Vinyl Coating (PVF2) of minimum dry film thickness (DFT) 20 microns over suitable primer. Inner face of the sheet shall be provided with suitable pre-coating of minimum DFT 7 microns over suitable primer. The permanent colour coated sheet shall meet the general requirements of IS : 14246 and shall conform to class 3 for the durability. | SQM | 14,500 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1505 | Designing, providing and fixing Inner sheet of Permanent colour coated metal cladding with troughed M.S. sheets of 0.6mm bare metal thickness having minimum yield strength 250 MPa and zinc-aluminium alloy coating not less than 275 gm/sqm total on both sides of both sheets including fixing to supports / rails by concealed fixing system, corrosion resistant self tapping / self drilling type fasteners with suitable cap, flashing etc. all complete. The exposed surface of the sheet shall be permanently colour coated with silicon modified polyester paint of minimum dry film thickness (DFT) 20 microns over suitable primer. Other face of the sheet shall be provided with suitable pre-coating of minimum DFT 7 microns over suitable primer. The permanent colour coated sheet shall meet the general requirements of IS : 14246 and shall conform to class 3 for the durability. The sheet shall be fixed directly to side runners and Z spacers as per IS : 277. The sheet shall be fixed at the rate not more than 1500mm center to center to hold the insulation and external sheeting. | SQM | 13,750 | | | | |
| 1506 | Providing and fixing insulation of resin bonded mineral wool of 50 mm nominal thickness conforming to IS 8183 having a density of 32 kg/cum glass wool or 48 kg/cum for rock wool, for cladding/under deck insulation including application of glue and tying with lacing wire, for glass/rock wool as per manufacturer's recommendations. | SQM | 13,750 | | | | |
| 1507 | Providing and fixing insulation of resin bonded mineral wool of 50 mm nominal thickness conforming to IS 8183 having a density of 32 kg/cum glass wool or 48 kg/cum for rock wool, for cladding/under deck insulation including wrapping in black polythene black supported over weld mesh 75X75X1.6 MM dia to hold in position and application of glue & tying with lacing wire, for glass/rock wool as per manufacturer's recommendation. | SQM | 2,349 | | | | |
| 1508 | Providing and installing under deck insulation of resin bonded mineral wool of 50 mm nominal thickness conforming to IS 8183 having a density of 32 kg/cum glass wool or 48 kg/cum for rock wool including wrapping using minimum 0.05 mm thick aluminium foil on exposed surface followed by 0.56 mm dia and 25 mm mesh GI wire netting, fixed at various elevations @ 600mm C/c with 14G steel wire or with rawl plugs as per direction of Engineer in charge. | SQM | 2,350 | | | | |
| 1600 FALSE CEILING | | | | | | | |
| False ceiling including all labour, material, equipment, transportation, handling, suspension system etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1601 | Providing and fixing glass fibre reinforced gypsum plaster board (GRG) ceiling (having gypsum core mixed with glass fibre in panels of size 600x600) system consisting of metal supporting grid system forming panels of specified size, suspended from RCC slab/structural steel or catwalkway grid above with 6 mm (minimum) galvanised wires (rods) with special height adjustment clips, including preperation of working drawing, providing openings for AC ducts, return air grills, light fixtures etc (but excluding the cost of catwalkway grid) all complete as per drawings, specification and instructions of the engineer. The suspension system shall consist of aluminium grid of 38x25x1.5 mm and cross tie of 25x25x1.5 mm and aluminium angle of 25x25x1.5 mm. | | | | | | |
| a | 12.5 mm thick GRG board with galvanised light gauge steel load bearing supporting GI frame and finished flat (seamless). | SQM | 125 | | | | |
| b | 12.5 mm thick GRG board in profile (dome ,curved profiled etc.) with galvanised light gauge steel load bearing supporting GI frame and finished smooth (seamless). | SQM | 45 | | | | |
| 1603 | Providing and fixing permanently colour coated aluminium false ceiling of approved colour and Luxalon 84 C or approved equivalent with corrosion resistant aluminium alloy panels of minimum thickness 0.5mm including 50mm thick mineral wool insulation(density 48 kg/cum) conforming to IS:8183 bound in polythene bags on top of panels. Additional hangers and height adjustment clips shall be provided for return air grills, light fixtures, A.C. ducts etc all complete. Suitable M.S. channel grid with minimum MC 100 shall also be provided above the false ceiling level for movement of personnel to facilitate maintenance of lighting fixtures, AC ducts etc. (Materials for structural platform grid made up of MS Channels/ Beams / Angles shall be supplied by BHEL and shall be paid under ST No 2301). The false ceiling suspension system shall consist of aluminium grid of 38x25x1.5 mm and cross tie of 25x25x1.5 mm and aluminium angle of 25x25x1.5 mm. | SQM | 3,335 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1605 | Providing, fixing and laying anodised natural colour matt finished aluminium false ceiling of Jindal/Hindalco make with corrosion resistance aluminium alloys panels of minimum thickness 0.5mm including 50mm thick mineral wool (density 48kg/cum insulation (as per IS:8183) bound in polythene bags on top of panels. Additional hangers and height adjustment clips shall be provided for return air grills, light fixtures. A.C. ducts etc. suitable M.S. channel (minimum MC 75) grid shall also be provided above the false ceiling level for movement of personnel to facilitate maintenance of lighting fixtures, AC ducts etc. The work to be complete as per specifications, drawings and direction of engineer. (Materials for structural platform grid for movement made up of MS Channels/ Beams / Angles shall be supplied by BHEL and shall be paid under ST No 2301) | SQM | 183 | | | | |
| 1700 RAIN WATER DOWN TAKE PIPES | | | | | | | |
| Rain water down take pipes including all labour, material, transportation, 2 coats of approved paint over one primary coat, fixtures, accessories etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 1707 | Providing and fixing GI down take pipes conforming to IS:1239 /IS:3589 of medium duty all complete for following diameters. | | | | | | |
| a | 100 mm Dia | RM | 175 | | | | |
| b | 150 mm Dia | RM | 1,800 | | | | |
| c | 200 mm Dia | RM | 1,200 | | | | |
| 1708 | Providing and fixing HDPE down take pipes conforming to IS:4984 as per specification of following diameters. | | | | | | |
| b | 160 mm Dia | RM | 200 | | | | |
| 1800 MISCELLANEOUS WORKS | | | | | | | |
| Miscellaneous works including all labour, material, equipment etc. at any level unless otherwise specified as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 1801 | Providing and Filling in trenches, plinths, area paving and other underground structures with graded stone aggregate of size range 63 mm to 45 mm in layers not exceeding 230 mm in thickness including breaking of stone boulders to required sizes, filling the interstices with selected sand and compacting to 85 % of original volume of stone stack for all lifts etc. all complete. Payment shall be made for the measurement of the volume of the compacted fill. | CUM | 450 | | | | |
| 1804 | Supply and installation of approved 25mm thick vibration damping resilient pads on/around foundation of vibrating equipment and at other locations all complete. | SQM | 50 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|---|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1805 | Providing 50mm thick premix carpet surfacing laid to slope in two layers 30mm and 20mm respectively with 12mm downgraded stone chips mixed with 80/100 grade bitumen @ 52 Kg/Cu.M including compaction etc. all complete. | SQM | 1,750 | | | | |
| 1806 | Providing 50mm thick anti corrosive layer laid to required slope consisting of clean & well graded coarse sand mixed with A90 grade bitumen for softening point upto 45 degree Celcius or A65 grade bitumen for softening point above 45 degree celcius as per IS: 73 or its equivalent quality 8 to 10% by volume and rolled or compacted all complete. | SQM | 1,750 | | | | |
| 1807 | Providing and fixing G.I strips minimum 1.5mm thk and 150mm wide including fixing accessories etc. all complete. | Kg | 225 | | | | |
| 1808 | Providing and fixing aluminium strips minimum 18 SWG thk and 300mm wide over expansion joints with minimum lap of 50mm length including brass / aluminium screws, rawl plugs etc. all complete. | RM | 75 | | | | |
| 1810 | Providing, laying and fixing rails and guide rails in concrete for transformer, rail track including cutting of rails, joining of rails, anchoring lugs etc all complete. | MT | 64 | | | | |
| 1811 | Providing and fixing weep holes in Drains consisting of 100 mm dia HDPE pipe sleeves with single side covering for the pipe mouth with galvanised welded wire fabric of 20 mm sq. opening covered with 40 mm downgraded aggregates in 300 X 300 mm sq. and 300 mm deep size all complete. | EACH | 175 | | | | |
| 1812 | Laying of earthing mats/rods including risers, transportation from yard stores, loading, unloading, cutting to length, welding, protective painting of joints etc. all complete. (Excavation & Back filling shall be paid separately under respective item of earth work. Earthing mats/rods shall be supplied by BHEL free of cost) | MT | 225 | | | | |
| 1815 | Providing and fixing GI rungs in concrete/brick walls having zinc coating of minimum 900 g/sqm etc. all complete. | Kg | 750 | | | | |
| 1816 | Providing and fixing PVC pressure release valve of minimum dia 90mm in water retaining structure including 160 mm dia housing pipe of minimum length 3.75 m with perforation as per IS4558, nylon jali, perforated end plug, collar, graded filter, excavation, fixing in concrete slab/wall etc. all complete. | EACH | 128 | | | | |
| 1817 | Providing and fixing HDPE pipes in concrete/ brick work of following sizes including cutting, fixing and levelling in position etc. all complete. | | | | | | |
| b | 100 mm dia | RM | 50 | | | | |
| c | 150 mm dia | RM | 50 | | | | |
| d | 200 mm dia | RM | 50 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|------|-------------------|------------|--|--------------|--|
| <div>  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant </div> | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 1819 | Design, supply, fabrication, erection of stoplog gates in CW Pumps with embedments required, lifting beams, special tools & plants, spare parts for three years, machining, casting, all materials such as structural steel, cast steel, stainless steel, brass used for seals, rubber seals, gears, ball and roller bearing, branch bushings, greasing, bolts, nuts, lugs, threaded fastners etc., cleaning, sand blasting, hot double dip galvanised with minimum coating of zinc 750 gms/sqm., following by an application of etching primer and dipping in black bitumen as per B.S. 3416, erection along with a second stage concreting to true plumb and levels, submission of drawings / fabrication drawings for engineers approval etc all complete. The leakage through rubber seal shall not be more than 5 lit/min/metre length of seal under maximum head.(only weight of structural steel including embedments shall be considered for payment purpose) (SS component shall be measured separately for payment) | MT | 60 | | | | |
| 1820 | SS component mentioned under ST No. 1819. | MT | 5 | | | | |
| 1821 | Supplying, fabricating, erecting in position and testing / examining bolted and / or welded structural steel work for stationary screens made out of rolled sections and / or plates including cutting, straightening if required, edge preparation, bolting / welding of joints, cleaning, sand blasting, hot double dip galvanised with minimum coating of zinc as 750 gms./sqm. followed by application of an etching primer and dipping in black bitumen as per BS 3416 etc all complete. | MT | 55 | | | | |
| 1825 | Supply and laying approved quality Stone aggregate 40mm size in transformer yards after treating with antiweed chemicals. | CUM | 25 | | | | |
| 1826 | Supply and laying approved quality gravels of 20mm size in transformer yards after treating with antiweed chemicals. | CUM | 15 | | | | |
| 1830 | Dismantling old existing structural steel work at any level including plates, bolts, cutting rivets, welding, dismembering and stacking the dismantled materials within a lead upto 1km etc all complete. | MT | 100 | | | | |
| 2000 FENCING AND GATES | | | | | | | |
| Fencing and gates including all labour, material, equipment etc at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2002 | Supplying and erecting in position 2.4 m high gavanised chain linked fencing conforming to IS 2761 of 10G hot dip galvanised steel wires woven in the form of zig-zag mesh giving an opening size of 50 mm square. GI barbed wire fencing of height of 600 mm conforming to IS 298 at top of chain link fencing shall be provided with 4 strands of barbed wire hot dip galvanised wire of 12G comprising of 2 ply of wires with barbs of 16G spaced at 100mm. Cost to include for GI hook bolts, rings & washers, hot dip galvanised tension wires, 25X6 mm GI flat stretcher bar at end posts, accessories etc. all complete. (Structural post shall be separately under ST No. 2007) | RM | 842 | | | | |
| 2007 | Supply and fixing of hot dip galvanised mild steel posts for fencing. Rate of zinc coating shall not be less than 710 g/m2 on steel posts. | MT | 6 | | | | |
| 2009 | Supply, fabrication and installing in position and testing galvanised MS Gates out of channels, joists, angles, flats, plates, pipes, welded steel wire mesh & sheets including stiffeners, bracings, fabricated hinges, MS Aldrops with locking arrangement, tempered steel pivot, guide track of MS Tee, bronze aluminium ball bearing arrangements, castor wheels, paintings etc. all complete. | MT | 4 | | | | |
| 2100 WATER SUPPLY | | | | | | | |
| Water supply work including men, material, equipment etc. at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 2101 | Providing and fixing in position tested heavy duty type chromium plated (CP) brass long neck bib cocks including sockets, union, nuts etc all complete - 15mm nominal bore. | EACH | 108 | | | | |
| 2103 | Providing and fixing in position heavy duty brass full way valve with wheel of approved quality including all specials etc all complete for following sizes: | | | | | | |
| a | 25mm nominal bore. | EACH | 54 | | | | |
| 2104 | Providing and fixing GI pipes class B medium class conforming to IS:1239 pipes shall be concealed and painted with anticorrssive paint, complete for internal works with GI sockets, unions, elbows, tees, nipples etc and clamps including cutting and making good the walls etc all complete for following sizes: | | | | | | |
| b | 20 mm nominal bore. | RM | 210 | | | | |
| 2105 | Providing and fixing GI pipes class B complete for external work with GI sockets, unions, elbows, tees, nipples etc including trenching & refilling, anti-corrosive paint etc all complete for following sizes: | | | | | | |
| c | 25 mm nominal bore. | RM | 274 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|---|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2106 | Providing and fixing 610mmx453mmx6mm thk mirror from reputed mirror manufacturer. Mirror shall be mounted with glass adjustable revolving CP brackets with CP screws etc all complete. | EACH | 10 | | | | |
| A2106 | Providing and fixing wall to wall bathroom float glass mirror of 6mm thk from reputed mirror manufacturer complete with all fittings, etc. | SQM | 45 | | | | |
| 2107 | Providing and fixing 610mmx127mmx6mm thk clear glass with C.P Guard rails and mounted on C.P. brackets etc all complete. | EACH | 83 | | | | |
| 2108 | Providing and fixing 25 mm diameter stainless steel towel rails (600mm X 25mm) all complete. | EACH | 26 | | | | |
| 2110 | Providing and fixing C.P. soap holder mounted with C.P. screws etc all complete. | EACH | 87 | | | | |
| 2111 | Providing and fixing stainless steel / C.P. liquid soap dispenser . Dispenser shall be round and easily revolving with removable threaded nozzle and mounted on C.P. brackets etc all complete. | EACH | 84 | | | | |
| 2112 | Providing and fixing glazed vitreous wall mounted paper holder with suitable cover cum cutter fitted with CP screws etc. sll complete. | EACH | 27 | | | | |
| 2113 | Providing and fixing chromium plated brass shower rose with 15 or 20 mm inlet all complete. | EACH | 13 | | | | |
| 2114 | Providing & fixing in position P.V.C. water tank of Syntex or approved equivalent as per IS:12701 including making all necessary inlet & outlet pipes, fixture, ball cocks, valves etc all complete for following capacities. GI pipes shall be paid separately under ST No. 2105. | | | | | | |
| b | 2000 litres capacity | EACH | 5 | | | | |
| c | 5000 litres capacity | EACH | 1 | | | | |
| 2115 | Providing and fixing approved stainless steel sink with integrated drainboard as per IS:13983 of size 915x460x178mm with CI brackets, stainless steel chain with rubber plug 40mm, cp brass waste trap with necessary union complete including painting the fittings, cutting and making good the wall where required etc. all complete. | EACH | 6 | | | | |
| A2116 | Providing and fixing Centrifugally Cast (Spun) Iron Pressure Pipes of Class LA as per IS:1536 for external work with all gaskets, jointing, hydro testing etc. complete including trenching & refilling, anti-corrosive paint etc all complete for following sizes: | | | | | | |
| a | 200 mm nominal bore. | RM | 50 | | | | |
| b | 300 mm nominal bore. | RM | 200 | | | | |
| c | 500 mm nominal bore. | RM | 50 | | | | |
| 2200 SANITARY WORKS | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| Sanitary work including all labour, material, equipment etc. at any level as per specification, drawings and as directed by engineer - in - charge. | | | | | | | |
| 2201 | Supply and fixing glazed vitreous china Wash Basin conforming to IS:2556 part 4 of oval shape with R.S. or C.I. brackets painted white, 15mm chromium plated brass hot & cold faucets with nylon washers, chromium plated brass chain with rubber plug, 32mm chromium plated brass bottle trap and waste of standard pattern, 32mm dia chromium plated brass trap unions, plastic connection pipe with chromium plated nuts, fittings, cutting and making good the walls where required etc all complete. | | | | | | |
| a | White | EACH | 15 | | | | |
| b | Colored | EACH | 15 | | | | |
| 2202 | Providing and fixing approved vitreous china laboratory sink of size 600x400x200mm conforming to IS:2556 (part-5) with R.S. or C.I. brackets, chromium plated brass chain with rubber plug 40mm, CP brass waste and 40mm CP brass trap with necessary union complete including painting the fittings, cutting and making good the wall where required etc. all complete. | EACH | 5 | | | | |
| 2203 | Providing and fixing stainless steel kitchen sink of size 610x510x200mm conforming to IS: 13983 including all fittings etc. all complete. | EACH | 3 | | | | |
| 2204 | Providing and fixing colour glazed vitreous china European type water closet conforming to IS:2556 with siphon, open front solid plastic seat and plastic cover, low level 12.5 litre PVC flushing cistern (same colour as WC) with valveless fittings, necessary C.P connections etc all complete. | | | | | | |
| a | Floor mounted | EACH | 12 | | | | |
| 2205 | Providing and fixing colour glazed vitreous indian type Orissa pattern (580x440mm) water closet conforming to IS:2556 part 3 with all fittings including foot rests, low level 12.5 litre PVC flushing cistern with valveless fittings, necessary C.P connections etc all complete. | EACH | 3 | | | | |
| 2206 | Providing and fixing white flat back glazed vitreous china urinals of size 440x265x355 mm with photo voltaic control flushing system as per IS:2556 (part 6, section 1) with flush pipes, lead pipes, gratings, traps and necessary C.P. fittings etc. all complete. | EACH | 52 | | | | |
| 2207 | Supply, laying and jointing UPVC pipes of class 3 as per IS:4985 including bends, branches and all other necessary fittings, M.S holder bats/clamps, cutting and making good the walls and floors, jointing, testing etc all complete for following. | | | | | | |
| c | 160mm dia pipes | RM | 75 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|---|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2208 | Providing, laying light duty non pressure NP3 class RCC pipes with collars jointed with stiff mixture of cement mortar 1:2 including testing of joints etc all complete for following. | | | | | | |
| b | 300mm dia | RM | 50 | | | | |
| c | 450mm dia | RM | 92 | | | | |
| b | 600mm dia | RM | 69 | | | | |
| e | 900mm dia | RM | 92 | | | | |
| 2209 | Providing, laying light duty non pressure NP2 class RCC pipes with collars jointed with stiff mixture of cement mortar 1:2 including testing of joints etc complete for following. | | | | | | |
| a | 150mm dia | RM | 125 | | | | |
| b | 250mm dia | RM | 100 | | | | |
| c | 300mm dia | RM | 50 | | | | |
| d | 500mm dia | RM | 25 | | | | |
| 2211 | Providing and fixing C.I Manhole heavy duty cover of size 600mmx450mm including frame from reputed manufacture etc. all complete. | EACH | 15 | | | | |
| 2212 | Providing and fixing circular heavy duty C.I. manhole cover of 600 mm dia with frame etc. all complete. | EACH | 20 | | | | |
| 2213 | Providing and fixing square mouth S.W Gully trap grade 'A' complete with CI grating, brick masonry chamber and water tight CI cover with 300x300mm (inside). The weight of cover to be not less than 4.53 Kg and frame to be not less than 2.72 Kg etc all complete for following sizes: | | | | | | |
| a | 100x100mm P or S Type. | EACH | 25 | | | | |
| 2214 | Providing and fixing square mouth S.W Gully trap grade 'A' complete with UPVC grating, brick masonry chamber and water tight CI cover with 300x300mm (inside). The weight of cover to be not less than 4.53 Kg and frame to be not less than 2.72 Kg etc all complete for following sizes: | | | | | | |
| a | 100x100mm P or S Type. | EACH | 15 | | | | |
| 2215 | Providing and fixing C.I. floor traps with C.P jalli all complete. | EACH | 100 | | | | |
| 2217 | Providing and installing approved brand single tap water cooler of 80 L cooling capacity all complete. | EACH | 3 | | | | |
| 2218 | Providing and installing approved brand single tap water cooler of 150 L cooling capacity all complete. | EACH | 3 | | | | |
| 2219 | Providing and fixing white vitreous urinal partitions of size 675x325x85mm all complete. | EACH | 25 | | | | |
| 2220 | Providing and fixing eye and face water fountain (combined unit with receptacle conforming to IS: 10592) all complete as per specification. | EACH | 6 | | | | |
| 2300 STRUCTURAL STEEL | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|------|-------------------|------------|--|--------------|--|
| <div>  Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant </div> | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| | Structural steel works including all labour, material, equipments, transportation, handling etc. at any level as per specification, drawings and as directed by engineer - in - charge. BHEL will supply Structural Steel as a free issue. Loading, transporting and unloading from BHEL stores at location described in specification shall be done by bidder. | | | | | | |
| 2301 | Fabrication and erection of structural steel with mild steel rolled section / built up section / combination of both conforming to Grade E250/E300 IS:2062, pipes conforming to IS:1161/ IS:1239, chequered plate conforming to IS: 3052, mild steel rounds, monorails, stays, safety chains, ladders, MS grating etc. in columns, beams, gantry girders, bunkers, silos, hoppers, roof trusses, portals, laced purlins, space frames, hangers, struts, monorails, galleries, stiffeners, wall beams, sheeting runners, brackets, stub columns, bracings, cleats, trestles, base plates, splice plates, chequered plate flooring, decking and seal plates, steel frame grid over false ceiling, walkway platforms, ladders, stairs, stringers, treads, landings, hand-rails etc including 2 coats of redoxide zinc-chromate primer as per IS:1477 (one coat at shop and one coat after erection), connection design & preparation of fabrication drgs, collection of steel from stores, fabrication, straightening, cutting, bending, rolling, grinding, machining, drilling, welding, compatible electrodes and other consumables, alignment, erection bolts & nuts (weight of erection bolts, nuts and welds not payable), assembly, edge preparation, preheating (min preheat and interpass temperature of 20o C for welding over 20 mm and upto 40 mm & 66o C for welding over 40 mm and upto 63 mm & 110o C for thickness over 63 mm & use of low hydrogen/ radiogenic electrodes), post heating, testing of welders, inspection of welds, visual inspection, non destructive and special testing, rectification and correction of defective welding works, production test plate, inspection and testing, erection scheme, protection against damage in transit, stability of structures, installation of temporary structures, setting column bases, surface preparation by means of manual or mechanical power tools as per IS:1477 part 1 and ST-2 as per SIS05-5900, touch-up painting, rectification, dismantling and removal of all temporary structures (weight of temporary structures not payable), return of surplus / waste steel materials to store etc all complete. Including appointment of a seperate agency, approved by BHEL, for review and approval of fabrication drgs, in consultation with BHEL. | MT | 17,266 | | | | |
| | | | | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|---|---------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2302 | Extra over ST NO. 2301 for blast cleaning of steel structures to near white metal surface(Sa 2 1/2) and applying epoxy based zinc phosphate primer in coats of minimum 25 micron (DFT) at shop and 25 micron (DFT) after erection, instead of primer coat of red oxide zinc-chromate, including touch-up painting etc all complete. | MT | 1,000 | | | | |
| 2303 | Extra over ST NO. 2301 for providing and application of two coats of primer consisting of chemical resistant epoxy resin and hardener (Minimum 1 Kg of primer mix shall be consumed for priming of 4 to 5 m2 area of surface) instead of primer coat of red oxide zinc-chromate, including touch up painting etc. all complete. | MT | 1,500 | | | | |
| 2304 | Providing and applying two coats of synthetic enamel paint as per IS:2932 with minimum 50 micron total dry film thickness (DFT) of approved make and shade to achieve an even shade over steel sections already having primer coats and keeping overall DFT with primer not less than 110 microns including protection and cleaning, scaffolding etc. all complete. | MT | 17,000 | | | | |
| 2305 | Providing and applying two coats of epoxy based colour finish paint with minimum 50 micron total dry film thickness (DFT) of approved make and shade to achieve an even shade over steel sections already having primer coats and keeping overall DFT with primer not less than 110 microns including protection and cleaning, scaffolding etc. all complete. | MT | 1,000 | | | | |
| 2307 | Supplying, fabrication, erection and alignment of factory made electroforged galvanised grating units with mild steel conforming to IS:2062 in flooring, platforms, drain and trench covers, walk-ways, passages, staircases with edge binding strips and anti-skid nosing in treads etc. including fixing clamps, fittings, fixtures, all taxes, duties, packing, grinding, drilling, welding, edge preparation, etc. all complete. | MT | 269 | | | | |
| 2310 | Providing and fixing in position of permanent mild steel bolts (class 4.6 as per IS : 1367 and grade 'C' as per IS: 1363) and nuts, washers etc. up to and inclusive of 39 mm diameter and upto 300mm long for structural steel work etc all complete. | Quintal | 37 | | | | |
| 2311 | Providing and fixing in positing of high strength structural bolts (of property class 8.8 and product grade 'C' as per IS: 1367) and conforming to IS: 3757 and high strength structural hardened and tempered nuts (of property class '8' as per IS:1367) conforming to IS:6623 with hardened and tempered washers as per IS:6649 etc. up to and inclusive of 39 mm diameter and upto 300 mm long for structural steel work etc all complete. | Quintal | 35 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2312 | Dismantling of steel structure , lowering of material and carriage of the dismantled material up to field fabrication shop / projects storage including temporary dismantling, cutting, re-welding, supporting, and restoring to correct position all temporarily dismantled members, re-alignment of all adjacent connected members to their correct positions (weight of such adjacent members and temporarily dismantled members not payable), scaffolding, staging, tools & tackles, gas cutting, welding, consumables etc all complete. | MT | 75 | | | | |
| 2313 | Addition to, alterations in and/or modification of "Erection Marks" including cutting of parts, gauging of welds, cutting, grinding, fabrication, welding, drilling holes, straightening, removal of bends, raising to the required level, painting, transportation, return of unutilised steel pieces to the project store, temporarily dismantling, cutting, re-welding, supporting and restoring to correct position of all the temporarily dismantled members, realignment of adjacent connected members (weight of such temporarily dismantled and adjacent members not payable) etc all complete for the following: | | | | | | |
| a | In erected position | MT | 13 | | | | |
| b | In fabrication yard | MT | 28 | | | | |
| 2314 | Re-erection of dismantled fabricated structural steel members including carriage of modified "Erection Marks" from the field fabrication shop to erection site, lifting to required posiion, aligning in position, tack welding, final welding and touch up painting including temporary dismantling and re-erection of temporarily dismantled members, cutting, rewelding, supporting and restoring to the correct position of all temporarily dismntatled members, re-alignment of adjacent connected members(weight of such temporarily dismantled members and adjacent members not payable), scaffolding, staging, tools & tackles, gas cutting, welding, consumables etc all complete. | MT | 24 | | | | |
| 2316 | Supply, fabrication and erection of minimum 3.15 mm thick stainless steel liner of grade AISI-304 ; Finish Grade 2B (Cold rolled, Annealed & Pickled and Skin passed) on M.S. plate for inside surfaces of hopper & mouth of hopper of bunkers including fixing with stainless steel studs, bolting (including countersunk), welding with electrode classification E308L for welding of stainless steel to stainless steel and E309 for stainless steel to mild steel etc. all complete. | MT | 185 | | | | |


SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|--|--|------|-------------------|------------|--|--------------|--|
|  Bill of Quantities for Complete Civil, Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2317 | Providing and fixing in position PTFE type sliding bearings of reputed manufacturer, individual bearing suitable for required vertical loads as per the construction drawings and for maximum displacement of ± 50 mm including all taxes, duties, transportation, installation, drilling, bolting, erecting, aligning etc all complete for following vertical loads. | | | | | | |
| a | 20 Tons | EACH | 19 | | | | |
| b | 25 Tons | EACH | 15 | | | | |
| c | 40 Tons | EACH | 8 | | | | |
| d | 50 Tons | EACH | 4 | | | | |
| e | 60 Tons | EACH | 8 | | | | |
| 2318 | Providing and fixing flexible open ended bellow strap of neoprene of minimum thickness 2 mm and minimum width 200 mm with aluminium stripped edges as sealing below top of bunker and bottom of tripper floor to avoid the coal dust nuisance all complete. | RM | 400 | | | | |
| 2319 | Supply, fabrication and fixing of stainless steel pipe hand railing of 32 mm/40 mm dia including transportation, loading/unloading etc. all complete.. | MT | 5 | | | | |
| 2321 | Conducting radiography test on welds wherever specified including equipments, measuring devices, gauges, test report etc. all complete. | RM | 125 | | | | |
| 2322 | Conducting ultasonic test on welds wherever specified including equipments, measuring devices, gauges, test report etc. all complete. | RM | 100 | | | | |
| 2323 | Conducting ultasonic test on steel plates as per ASTM-A435 or equivalent wherever specified including equipments, measuring devices, gauges, test report etc. all complete. | SQM | 300 | | | | |
| 2324 | Conducting magnetic particle test on welds wherever specified including equipments, measuring devices, gauges, test report etc. all complete. | RM | 88 | | | | |
| 2325 | Conducting dye penetration test on welds wherever specified by the engineer including provision of necessary equipments, measuring devices, gauges etc. all complete (over and above the work already specified in the specifications.) | RM | 175 | | | | |
| A2326 | Supply, fabrication and erection of handrail shop fabricated with 32mm diameter GI pipe (medium class) using 360gm/sqm of zinc coating as per IS:1161. 5.2 . Handrailing shall be a two-rail system with the top rail 1000 mm above the walkway surface and the intermediate rail 450 mm below the top rail. | MT | 13 | | | | |
| A2327 | Supply, fabrication and erection of aluminium handrail top over flat fixed on MS Square balustrades. MS balustrades and flat shall be paid separately under item 2301. | RM | 150 | | | | |
| 2400 ROAD WORKS | | | | | | | |

SIGNATURE OF BIDDER

|  | TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | |
|--|--|------|-------------------|------|-------|--------------|--|
| | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE | (INR) | AMOUNT (INR) | |
| | Providing Road Work including necessary material, labour, machinery, transportation etc as per specification, drawing, relevant IRC & IS codes and as directed by the Engineer-in-charge for the following. | | | | | | |
| 2401 | Preparation of sub grade by excavating earth to required depth for all types of soil/ rock, dressing to camber and consolidating the base including making good the undulation etc and disposal of surplus earth within a lead upto 1 km etc. all complete. | CUM | 12500 | | | | |
| 2403 | Providing, stacking & laying granular morrum for shoulder including watering, compaction with road roller to required camber etc all complete. | CUM | 1500 | | | | |
| A2406 | Providing , laying ,spreading & compacting Wet Mix macadam sub base/base course using graded crushed stone aggregates and material etc confirming to clause No. 406 of " Specification for Roads and Bridges works of MORT & H ." all complete. | CUM | 10000 | | | | |
| 2407 | Providing & applying tack coat of low viscosity liquid bitumen of grade 80/100 confirming to IS 73, 217 or 454 as applicable @10 kg/ 10 sqm for untreated WBM surface including scraping, cleaning with compressed air etc all complete. | SQM | 20500 | | | | |
| 2408 | Providing & applying tack coat of low viscosity liquid bitumen of grade 80/100 confirming to IS 73, 217 or 454 as applicable @ 6 kg/ 10 sqm for bituminous surface including cleaning with compressed air etc all complete. | SQM | 20500 | | | | |
| A2409 | Providing, mixing and laying of compacted 70 thk. Dense Bituminous Macadam (DBM) Course . Bitumen shall be of a suitable grade and aggregates, binder material as specified in specification including hot mixing, hot laying, rolling all complete. | SQM | 20500 | | | | |
| A2410 | Providing, mixing and laying Bituminous Concrete of compacted 40 mm thickness composed of suitable small size aggregate premixed with a bituminous binder on a prepared base. Mixing applying rolling as per IRC specification. | SQM | 20500 | | | | |

SIGNATURE OF BIDDER

| TENDER SPECIFICATION BHEL PSSR SCT 1467 2x800 MW YERMARAS THERMAL POWER STATION | | | | | | | |
|---|--|--|-------------------|------------|--|--------------|--|
|  | | Bill of Quantities for Complete Civil,Structural and Architectural Works per unit for 2x800MW Yermarus Thermal Power Plant | | | | | |
| ST. NO | DESCRIPTION OF ITEM | Item | Quantity per unit | RATE (INR) | | AMOUNT (INR) | |
| 2411 | Providing and applying liquid seal coat comprising of an application of a layer of bituminous binder using medium setting grade bitumen at the rate of 9.8kg/10sqm followed by a cover of stone chips at the rate of 0.09 cum/10sqm including rolling etc all complete. | SQM | 20500 | | | | |
| 2412 | Supplying and laying 400mmx150mmx350mm deep precast concrete kerb stone of grade M-20 with 20 mm nominal size stone aggregate and of shape as per detailed drawing including fixing with cement mortar (1:2) in 13mm thick joints, finishing of joints with neat cement paste, making drainage opening where required etc all complete. | RM | 4000 | | | | |
| 2414 | Supply and laying 150mm dia R.C.C NP-2 type Hume pipe in raised shoulders as rain water drains as per detailed drawing including fixing with cement mortar (1:2) in 13mm thick joints, finishing of joints with neat cement paste etc all complete. | RM | 25 | | | | |
| A2414 | Providing, laying light duty non pressure NP3 class RCC pipes with collars jointed with stiff mixture of cement mortar 1:2 including testing of joints etc. as per specifications for dia: | | | | | | |
| i) | 150mm | RM | 50 | | | | |
| ii) | 250mm | RM | 150 | | | | |
| iii) | 300mm | RM | 500 | | | | |
| iv) | 400mm | RM | 100 | | | | |
| v) | 500mm | RM | 50 | | | | |
| vi) | 600mm | RM | 25 | | | | |
| MISCELLANEOUS | | | | | | | |
| 2426 | Providing & laying 75 mm thick precast interlocking concrete pavers of approved colour and pattern as per specification and recommendation of manufacturer. | SQM | 4000 | | | | |
| 2427 | Providing and laying 50mm thick sand layer below concrete pavers including compaction etc all complete as per specification, drawing and as directed by Engineer. | SQM | 4000 | | | | |
| TOTAL | | | | | | | |

SIGNATURE OF BIDDER